

(19) World Intellectual Property
Organization
International Bureau



10/533540

(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/040606 A3

(51) International Patent Classification: H03K 17/96,
G06F 3/033

Brand, Mami [GB/GB]; 123 Hamilton Road, London
NW1 9EG (GB).

(21) International Application Number:
PCT/GB2003/004709

(74) Agent: ATKINSON, Ralph; Atkinson Burrington, 27-29
President Buildings, President Way, Sheffield S4 7UR
(GB).

(22) International Filing Date: 31 October 2003 (31.10.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0225315.1 31 October 2002 (31.10.2002) GB
0225316.9 31 October 2002 (31.10.2002) GB

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): HM
TECHNOLOGY INTERNATIONAL LIMITED
[GB/GB]; Unit 18, Wadsworth Business Centre, 21
Wadsworth Road, Perivale, Middlesex UB6 7JD (GB).

(72) Inventor; and


Published:

(75) Inventor/Applicant (*for US only*): MAMIGONIAN, —

with international search report

[Continued on next page]

(54) Title: MECHANICALLY OPERABLE ELECTRICAL DEVICE



(57) Abstract: Mechanically Operable Electrical Device A mechanically operable electrical device (102), comprising a transmitter electrode (302), a receiver electrode (312) and a moveable conductive element (201). The device is configured such that the conductive element is moveable to a first position remote from said electrodes such that the transmitter electrode is capacitance coupled to said receiver electrode, and the conductive element is moveable to a second position closer to the electrodes such that the capacitance coupling is reduced.